

## **UAS D-600 Specifications**

Model		D-600
Frame	Number of Rotors	6
	Dimensions	Height 530 mm
	Wingspan ø	980 mm
	Drone Weight	3.7 kg (6.5 kg with battery)
Electric Motor	Brushless	6 units
	KV	330 KV
	Max. Power	650 W
Rotor Blades	Material	Carbon fiber
	Dimensions	215 mm
Launch and Landing	Automatic Landing	Yes
	Foldable Gear	No
Operation	Max. Payload	8.5 kg
	Max. Speed	70 km/h
	Cruise Speed	5 m/s
	Control Range	5 km (max.)
	Endurance	25 min (with a Gimbal + SONY a5000)
	Max. Altitude	500 m
	Max. Climb Rate	12 m/s
	Wind Loading	12 m/s
	Configuration Software	Mission planner
Power Source	Battery	22,000 mAh 22.2V 25C 6S1P
	Nos. of Battery	1x
	Weight of Battery	2,509 g
Environment	Min. Operation Temperature	-20 °C
	Max. Operation Temperature	+65 °C
FPV	Real Time Image Link	Yes
	Frequency	5.8 GHz
	Power	600 mW
	Monitor	Included
Navigation Sensors	Sensors for Position / Orientation	GPS, IMU
	Accuracy	Vertical: ± 0.5 m Horizontal: ± 1 m
FCC Autopilot	Hardware Specification	P9X
	Software	Tower
Imaging Devices		_
	Type of Camera	Morror less / SLR
	Recommended camera	SONY a5000 (Approx 4.2 kg: with Gimbal)
Standard Accessories		Gimbal
		Propositional controller Futaba T14SG
		Camera set SONY a5000 with a lens
		Battery charger
		Carrying case

Precise Aerial Imaging System is dedicated to providing customers with first class aerial imaging system products and freedom of choice. We have carefully designed high-quality products to meet the needs of today's surveyors based on the experience of many years involved in product design and construction. We are committed to ease of use, a low cost of ownership and flexibility to accommodate  $different \ working \ environments. Our \ close \ partners \ are \ carefully \ chosen \ and \ are \ committed \ to \ these$ values as we are.

TI Asahi Co., Ltd. International Sales Department 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi Saitama, 339-0073 Japan Tel.: +81-48-793-0118 Fax. +81-48-793-0128 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer







Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.