## PENTAX | M-60/M-100 Series

# **Smart, and Accurate Hand-held Distance Meter**

- Flexible Range:
   60m (M-60) /
   100m (M-100) quick laser measurement within
   3 seconds
- Long Battery Life:
   5000 measurements with
   2 AA batteries
- Slope:
  Built in tilt sensor,
  automatically detects the slope (±45°) (M-100)
- Smart Multi Functions:

   Built in area and volume
   calculation system,
   and many other functions
   for a smooth workflow
- Any Environment: Protection against water and dust (IP54)





### **PENTAX**

#### **Technical Specifications M-60/M-100**

Model		M-60	M-100
Range		0.05 to 60m	0.05 to 100m
Minimum Range		1mm	
Measuring Accuracy		±2mm	
Measuring Time		Within 3 seconds	
Slope		Circulator Vial	Tilt sensor
	Slope Accuracy	_	±3°
	Slope Range	_	±45°
Battery		AA battery x2	
	Battery Life	Approximately 5000 Individual measurements (Alkaline)	
Environment		IP54 Water and dust resistant	
Safeguard Systems		Auto power off	
		Alarm display for remaining battery	
		Alarm display fo	or temperature
Operating Temperature		0°c ~ 40°c	
Weight		100g	150g
Other Systems		Area calculating	
		Volume calculation	
		Continuous measurement	
		Height measurement	
		Addition/Subtraction	
		Maximum/Minimum measurement	
		Saving measurement result to storage	
			Horizontal distance conversion

<sup>\*</sup> Specifications are subject to change without notice

#### NOTE:

\*This instrument is for indoor use only and not fit for outdoor use under direct sunlight.

TI Asahi Co., Ltd. International Sales Department 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi Saitama, 339-0073 Japan Tel.:+81-48-793-0118

Fax. +81-48-793-0128

E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer





Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.