

PENTAX

**Total Surveying
Solutions**

R-2800N Series

R-2801N | R-2802N | R-2803N | R-2805N

- + Long EDM range:
reflectorless up to 800 m
and in prism mode up to 3,000 m
- + Large internal memory:
60,000 points
- + Dual display
- + Easy transfer to a PC via SD card,
USB mini and RS-232C data port
- + Pre-loaded versatile
software functions
- + Dual battery system
for long time use



TI Asahi Co.,Ltd
Aiming at the future together!

TOTAL STATION SPECIFICATIONS

Model		R-2801N	R-2802N	R-2803N	R-2805N	
Telescope	Image			Erect		
	Magnification			30 x		
	Effective Aperture			45 mm		
	Resolving Power			3.0"		
	Field of View			1°25'		
	Minimum Focus			1.0 m		
	Focus			Manual		
	Laser Class			Visible Laser: Class IIIa (Reflectorless, sheet) / Class I (Prism)		
	Measurement Range	(Good condition) *3				
		Reflectorless *1			1.5 m ~ 800 m	
Reflector Sheet *2				1.5 m ~ 800 m		
Mini Prism				1.5 m ~ 800 m		
1P				1.5 m ~ 3,000 m		
3P				1.5 m ~ 4,000 m		
Accuracy	Prism			± (2 + 2 ppm x D) mm (Standard) ± (1.5 + 2 ppm x D) mm (Optional)		
	Reflector Sheet			± (3 + 2 ppm x D) mm		
	Reflectorless			2.0 m ~ 200 m: ± (3 + 2 ppm x D) mm 200 m ~ 300 m: ± (5 + 2 ppm x D) mm 300 m ~ 500 m: ± (10 + 2 ppm x D) mm 500 m ~ 800 m: ± (20 + 10 ppm x D) mm		
	Minimum Count			0.1 mm (Fine mode), 1 mm (Normal mode), 10 mm (Track mode)		
	Measurement Time *4	Repeat Meas.	Fine (0.1 mm)		Prism / Ref. Sheet 3.0 sec., Ref. less 3.0 sec. (over 300 m 5.0 sec.)	
Normal (1 mm)				Prism / Ref. Sheet 2.0 sec., Ref. less 2.0 sec. (over 300 m 4.0 sec.)		
Track (10 mm)				Prism / Ref. Sheet 0.4 sec., Ref. less 0.4 sec. (over 300 m 0.4 sec.)		
Initial Meas.		Fine (0.1 mm)		1.5 ~ 300 m 3.5 sec., over 300 m ~ 13 sec.		
		Normal (1 mm)		1.5 ~ 300 m 2.4 sec., over 300 m ~ 12 sec.		
		Track (10 mm)		1.5 ~ 300 m 2.5 sec., over 300 m ~ 12 sec.		
Angle Measurement	Measuring Method			Absolute rotary encoder		
	Detection Method			Vertical / Horizontal angle		
				2 sides		
	Minimum Count			1" / 5"		
	Accuracy (ISO17123-3)	1"	2"	3"	5"	
Compensator				2 axis		
Compensator Range				3' 30"		
Tangent Screw				1 Speed / Clamping (< 30")		
Sensitivity of Vials	Plate Level			30"/1 div. (electrical)		
	Circular Level			8/2 mm		
Plummet				Visible Laser, ± 0.5 mm (instrument height 1.5 m)		
Base				Detachable		
Dust and Water Protection				IP55 (instrument only)		
Ambient Temperature				-20°C ~ 50°C / -4°F ~ 122°F (Working range)		
Tripod Thread				5/8" x 11		
Dimensions/Weight	Dimensions			183 (W) x 342 (H) x 167 (L) mm		
	Weight (incl. Battery)			5.4 kg		
Carrying Case				440 (W) x 370 (H) x 275 (L) mm / 3.9 kg		
Battery Pack	Power Source			Li-ion 3,350 mAh x 2 = 6,700 mAh (hotswap)		
	Operation Time			Continuous approx. 8 hrs (ETH+EDM) with approx. 2.5 hrs of charging time		
	Weight			5,400 g		
Battery Charger and AC Adapter						
	Input Voltage (AC05)			AC 100 ~ 240V		
	Output Voltage (BC05)			DC8.4V		
Data Process	Data Recording Method			Internal Memory		
	Capacity / Coordinates Data			Up to 2GB / 60,000		
	Special Function			PowerTopoExpress 2		
	I/F			RS-232C, SD CARD, USB mini, Bluetooth (Class1)		
Display / Keyboard	Display Type			Graphic LCD / 20 characters x 8 lines / 240 x 96 pixels		
	Quantity			2		
	Keys			22 each (12 numeric / 5 function / 5 special)		
Display Back Light				Intensity settings: 10 steps		
Laser Pointer				Yes		
Date Clock				Yes		

* Designs and specifications are subject to change without notice. - Printed in Belgium - LEAF-R2800N-EN-1808 - © PENTAX 2018

- *1 The measurement range and accuracy of reflectorless, and time required to measure may vary by the shape, size of surface area and reflection rate of the target and its environment.
The measurement range of reflectorless is determined by the white side of the Kodak Gray Card.
- *2 Reflector sheet: Genuine Reflector sheet
- *3 The measurement range may vary by conditions of the environment.
Normal conditions: 20km visibility with slight shimmer
Good conditions: 40km visibility with overcast, no heat, no shimmer and moderate wind.
- *4 EDM measuring time is determined in good conditions. It may takes longer than usual to measure the distance exceeding 4000m in prism mode and 300m in reflectorless mode.

TI Asahi Co., Ltd.
International Sales Department
 4-3-4 Ueno Iwatsuki-Ku, Saitama-Shi
 Saitama, 339-0073 Japan
 Tel.: +81-48-793-0118
 Fax: +81-48-793-0128
 E-mail: International@tiasahi.com

www.pentaxsurveying.com/en/

Your Official Pentax Dealer



The CE marking assures that this product complies with the requirements of the EC directive for safety.

JSIMA
 Japan Surveying Instruments Manufacturers' Association

Member symbol of the Japan Surveying Instruments Manufacturers' Association representing the high quality surveying products.

